

**CLAIMS**

What is claimed is:

1. A method for configuring a semiconductor chip, the  
5 method comprising:

selecting a private cryptographic key;

selecting a public cryptographic key, wherein the  
public cryptographic key and the private cryptographic key  
are not related by a cryptographic key pair relationship;

10 and

embedding the private cryptographic key and the public  
cryptographic key in a read-only memory on the semiconductor  
chip.

15 2. The method of claim 1 wherein the semiconductor chip  
provides interface processing at a client.

3. The method of claim 1 wherein the embedding step  
further comprises the embedding of a serial number  
20 associated with the semiconductor chip.

4. The method of claim 3 further comprising:  
storing the public cryptographic key in a database in  
association with the serial number.

25 5. The method of claim 1 wherein the private cryptographic  
key, and the public cryptographic key in the read-only  
memory are inaccessible to an input/output connection of the  
semiconductor chip.

6. An article of manufacture comprising:

a first read-only memory structure containing an  
embedded private cryptographic key; and

5 a second read-only memory structure containing an  
embedded public cryptographic key, wherein the public  
cryptographic key and the private cryptographic key are not  
related by a cryptographic key pair relationship.

10 7. The article of manufacture of claim 6 wherein the  
article of manufacture is a semiconductor chip.

8. The article of manufacture of claim 7 wherein the  
semiconductor chip is capable of providing interface  
processing at a client.

15 9. The article of manufacture of claim 8 wherein the first  
read-only memory structure and the second read-only memory  
structure are contained within a cryptographic unit of a CPU  
chip.

10. A method for secure communication between a client and a server in a data processing system, the method comprising:

generating a client message at the client;

retrieving an embedded server public key from a

5 read-only memory structure in an article of manufacture in the client;

encrypting the client message with the embedded server public key; and

sending the client message to the server.

10

11. The method of claim 10 further comprising:

retrieving client authentication data;

retrieving an embedded client private key from a

read-only memory structure in an article of manufacture in

15 the client;

encrypting the client authentication data with the embedded client private key; and

storing the encrypted client authentication data in the client message.

20

12. The method of claim 11 further comprising:

retrieving an embedded client serial number from a read-only memory structure in an article of manufacture in the client; and

5 storing a copy of the embedded client serial number in the client message.

13. An apparatus for secure communication between a client and a server in a data processing system, the apparatus  
10 comprising:

means for generating a client message at the client;

means for retrieving an embedded server public key from a read-only memory structure in an article of manufacture in the client;

15 means for encrypting the client message with the embedded server public key; and

means for sending the client message to the server.

14. The apparatus of claim 13 further comprising:

20 means for retrieving client authentication data;

means for retrieving an embedded client private key from a read-only memory structure in an article of manufacture in the client;

25 means for encrypting the client authentication data with the embedded client private key; and

means for storing the encrypted client authentication data in the client message.

15. The apparatus of claim 14 further comprising:  
means for retrieving an embedded client serial number  
from a read-only memory structure in an article of  
manufacture in the client; and

5 means for storing a copy of the embedded client serial  
number in the client message.

16. A computer program product in a computer-readable  
medium for use in a data processing system for secure  
10 communication between a client and a server, the computer  
program product comprising:

instructions for generating a client message at the  
client;

15 instructions for retrieving an embedded server public  
key from a read-only memory structure in an article of  
manufacture in the client;

instructions for encrypting the client message with the  
embedded server public key; and

20 instructions for sending the client message to the  
server.

17. The computer program product of claim 16 further  
comprising:

25 instructions for retrieving client authentication data;  
instructions for retrieving an embedded client private  
key from a read-only memory structure in an article of  
manufacture in the client;

instructions for encrypting the client authentication  
data with the embedded client private key; and

30 instructions for storing the encrypted client  
authentication data in the client message.

18. The computer program product of claim 17 further comprising:

instructions for retrieving an embedded client serial number from a read-only memory structure in an article of manufacture in the client; and

instructions for storing a copy of the embedded client serial number in the client message.

19. A method for secure communication between a client and a server in a data processing system, the method comprising:

generating a server message at the server;

retrieving information that was requested by the client;

storing the retrieved information in the server message;

retrieving a client public key, wherein the client public key corresponds to an embedded client private key in a read-only memory structure in an article of manufacture in the client;

encrypting the server message with the client public key; and

sending the server message to the client.

20. The method of claim 16 further comprising:

retrieving server authentication data;

retrieving a server private key;

encrypting the server authentication data with the server private key; and

storing the encrypted server authentication data in the server message.

21. An apparatus for secure communication between a client and a server in a data processing system, the apparatus comprising:

means for generating a server message at the server;

5 means for retrieving information that was requested by the client;

means for storing the retrieved information in the server message;

10 means for retrieving a client public key, wherein the client public key corresponds to an embedded client private key in a read-only memory structure in an article of manufacture in the client;

means for encrypting the server message with the client public key; and

15 means for sending the server message to the client.

22. The apparatus of claim 21 further comprising:

means for retrieving server authentication data;

means for retrieving a server private key;

20 means for encrypting the server authentication data with the server private key; and

means for storing the encrypted server authentication data in the server message.

23. A computer program product in a computer-readable medium for use in a data processing system for secure communication between a client and a server, the computer program product comprising:

- 5       instructions for generating a server message at the server;
  - instructions for retrieving information that was requested by the client;
  - instructions for storing the retrieved information in
  - 10       the server message;
  - instructions for retrieving a client public key, wherein the client public key corresponds to an embedded client private key in a read-only memory structure in an article of manufacture in the client;
  - 15       instructions for encrypting the server message with the client public key; and
  - instructions for sending the server message to the client.
- 20   24. The computer program product of claim 23 further comprising:
- instructions for retrieving server authentication data;
  - instructions for retrieving a server private key;
  - instructions for encrypting the server authentication
  - 25       data with the server private key; and
  - instructions for storing the encrypted server authentication data in the server message.



25. A method for secure communication between a client and a server in a data processing system, the method comprising:

receiving a client message from the client;

retrieving a server private key;

5 decrypting the client message with the server private key;

retrieving a client serial number from the decrypted client message; and

10 retrieving a client public key that is associatively stored with the retrieved client serial number, wherein the client public key corresponds to an embedded client private key in a read-only memory structure in an article of manufacture in the client.

15 26. The method of claim 25 further comprising:

retrieving encrypted client authentication data from the client message;

decrypting the client authentication data with the retrieved client public key; and

20 verifying the decrypted client authentication data.

27. An apparatus for secure communication between a client and a server in a data processing system, the apparatus comprising:

- means for receiving a client message from the client;
- 5 means for retrieving a server private key;
- means for decrypting the client message with the server private key;
- means for retrieving a client serial number from the decrypted client message; and
- 10 means for retrieving a client public key that is associatively stored with the retrieved client serial number, wherein the client public key corresponds to an embedded client private key in a read-only memory structure in an article of manufacture in the client.

28. The apparatus of claim 27 further comprising:

- means for retrieving encrypted client authentication data from the client message;
- means for decrypting the client authentication data
- 20 with the retrieved client public key; and
- means for verifying the decrypted client authentication data.

29. A computer program product in a computer-readable medium for use in a data processing system for secure communication between a client and a server, the computer program product comprising:

- 5       instructions for receiving a client message from the client;
- instructions for retrieving a server private key;
- instructions for decrypting the client message with the server private key;
- 10       instructions for retrieving a client serial number from the decrypted client message; and
- instructions for retrieving a client public key that is associatively stored with the retrieved client serial number, wherein the client public key corresponds to an
- 15       embedded client private key in a read-only memory structure in an article of manufacture in the client.

30. The computer program product of claim 29 further comprising:

- 20       instructions for retrieving encrypted client authentication data from the client message;
- instructions for decrypting the client authentication data with the retrieved client public key; and
- instructions for verifying the decrypted client
- 25       authentication data.

31. A method for secure communication between a client and a server in a data processing system, the method comprising:

receiving a server message from the server;

retrieving an embedded client private key from a

5 read-only memory structure in an article of manufacture in the client; and

decrypting the server message with the embedded client private key.

10 32. The method of claim 31 further comprising:

retrieving encrypted server authentication data from the server message;

retrieving an embedded server public key from a read-only memory structure in an article of manufacture in the client; and

15 decrypting the server authentication data with the embedded server public key; and  
verifying the decrypted server authentication data.

20 33. The method of claim 32 further comprising:

retrieving requested information from the server message; and

25 in response to a determination that the decrypted server authentication data was verified, processing the requested information.

34. An apparatus for secure communication between a client and a server in a data processing system, the apparatus comprising:

means for receiving a server message from the server;  
5 means for retrieving an embedded client private key from a read-only memory structure in an article of manufacture in the client; and  
means for decrypting the server message with the embedded client private key.

10 35. The apparatus of claim 34 further comprising:

means for retrieving encrypted server authentication data from the server message;  
means for retrieving an embedded server public key from  
15 a read-only memory structure in an article of manufacture in the client; and  
means for decrypting the server authentication data with the embedded server public key; and  
means for verifying the decrypted server authentication  
20 data.

36. The apparatus of claim 35 further comprising:

means for retrieving requested information from the server message; and  
25 means for processing the requested information in response to a determination that the decrypted server authentication data was verified.

37. A computer program product in a computer-readable medium for use in a data processing system for secure communication between a client and a server, the computer program product comprising:

5 instructions for receiving a server message from the server;

instructions for retrieving an embedded client private key from a read-only memory structure in an article of manufacture in the client; and

10 instructions for decrypting the server message with the embedded client private key.

38. The computer program product of claim 37 further comprising:

15 instructions for retrieving encrypted server authentication data from the server message;

instructions for retrieving an embedded server public key from a read-only memory structure in an article of manufacture in the client; and

20 instructions for decrypting the server authentication data with the embedded server public key; and

instructions for verifying the decrypted server authentication data.

25 39. The computer program product of claim 38 further comprising:

instructions for retrieving requested information from the server message; and

30 instructions for processing the requested information in response to a determination that the decrypted server authentication data was verified.